(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

## (19) World Intellectual Property Organization

International Bureau

(43) International Publication Date

22 January 2004 (22.01.2004)



## Rec'd PST/PTO 1 2 JAN 2005

PCT

(10) International Publication Number WO 2004/008045 A1

(51) International Patent Classification<sup>7</sup>: 39/00, F28D 15/00

F25B 9/14,

(21) International Application Number:

PCT/BR2003/000097

(22) International Filing Date: 15 July 2003 (15.07.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: PI 0202997-9

16 July 2002 (16.07.2002) BR


- (71) Applicant (for all designated States except US): EM-PRESA BRASILEIRA DE COMPRESSORES S/A EMBRACO [BR/BR]; Rua Rui Barbosa, 1020, 89219-901 JOINVILLE - SC (BR).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): PEREIRA,

Roberto, Horn [BR/BR]; Rua Wolfgang Amon, 253, 89217-350 JOINVILLE - SC (BR). MAYKOT, Reinaldo [BR/BR]; Rua Max Colin, 239 - Apt. 404, 89204-040 JOINVILLE - SC (BR).

- (74) Agents: ARNAUD, Antonio, M. P et al.; Rua José Bonifácio, 93 9th floor, 01003-901 São Paulo SP (BR).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: REFRIGERATION SYSTEM



\_\_(57) Abstract: A refrigeration system comprising: a Stirling machine (1); a refrigerating chamber (4); a first thermal energy transfer device (2) operatively associated with a refrigerating portion (1b) of the machine and with the refrigerating chamber (4); a second thermal energy transfer device (3) operatively associated with a heat receiving means, external to said machine, and with the heating portion (1a) thereof, the first thermal energy transfer device (2) comprising: at least one capillary pump (10) mounted in the refrigerating chamber (4) to evaporate, by the heat absorbed from the latter, the circulating fluid received in said capillary pump (10); a condenser (20) operatively coupled to the refrigerating portion (1b) of the Stirling machine (1) to condense the circulating fluid received, in the gaseous state,, from the capillary pump (10); and pipes (30, 40) to conduct in a closed loop, the circulating fluid between the capillary pump (10) and the condenser (20).